

Drying cabinet

TS560

Features and benefits

- A drying cabinet is used to efficiently dry bulky or sensitive items
- No mechanical action - suitable for all kinds of garments such as gloves, shoes and delicate garments like silk and linen
- Extended lifetime of sensitive garments/work wear
- Time saving when used instead of flat or hang drying
- Ergonomic design - user friendly positioning of door handle and control panel, suitable for disabled users
- Safety:
 - Option of activating child safety start lock
 - Magnetic edge of doors eliminates risk of children being locked in
- Door circuit breaker which interrupts the drying process when the door is opened
- Insulated doors for quiet operation and robust design
- Easy operation:
 - 2 automatic drying programs will stop once the load is dry
 - 30 extensible hangers for easy loading/unloading
- Flexible installation:
 - Adjustable feet
 - Reversible door - left or right hanging



Options

- Shoe rack to make it easier to dry shoes and boots
- Glove hanger for more efficient drying of gloves, hats etc.
- Wall instruction can be found on Electrolux Professional Website

Main specifications		TS560
Rated capacity	kg	4
Evaporation*	g/min	19
Drying time cotton*	min	105
Rated input	kW	1.5
Energy/load of linen	kWh/kg	0.6
Energy/water evaporated	kWh/l	1.27

* Applies to 4 kg dry weight cotton with 50% residual moisture.

Electrical connection		TS560
Voltage		
230V 1AC 50-60 Hz kW(A)		1.5(10)
Connections		
Outlet	ø mm	100
Evacuated air quantity	m ³ /h	50
Sound level		
Sound pressure level*	dB(A)	<70
Weight		
	netto kg	56
Dimensions in mm		
A	Width	595
B	Depth	606
C	Height	1901
D		1915
E		15
F		60
G		255
H		1089
I		300
J		100
1 Operating panel		
2 Air outlet**		

Colour of front and side panels:
 blue (NCS S2050-R90B), (RAL 250 6030)
 light grey (NCS S3005-R80B), (RAL 260 7005)

* A-weighted emission sound pressure level at workingstations

** Connected with supplied drive interruption and hose

