



# Spotting Tables

## FSU1, FSU2, FSU3



Model FSU1 shown  
*Photo non contractuelle*



Model FSU3 shown  
*Photo non contractuelle*

### Features and benefits

- Corrosion resistant table for pre and post spotting
- Steam/air spotting gun removes spots
- Cold spotting guns which remove spots and are safe to use
- Air drying gun, dries the fabric

### Main options

- Integral suction fan simplifies installation
- Steam/air spotting gun removes spots
- Cold spotting gun removes spots and is safe to use
- Suction cabinet improves the working environment
- Ecological filter (active carbon) reduces solvent fumes in the working area
- Integral/optional air compressor simplifies installation

FSU1	FSU2	FSU3
------	------	------

X	X	X
-	-	X
X	-	-
X	-	X

X	X	X
X	X	-
-	X	X
X	X	X
X	X	X
X	X	-

x available

- not available



Electrical connections		FSU1	FSU2	FSU3
Voltage				
208-240V 1 AC 50/60 Hz	kW	0.25*	0.25***	0.25***
230/400-415V/3V 3N 50/60 Hz	kW	1.75**	1.75**	-
Steam, air and vacuum connection				
Steam	DN	-	-	15
Rec. steam pressure	kPa	-	-	400-500
Steam consumption	kg/h	-	-	5-10
Condensate	DN	-	-	15
Compressed air	DN	6	-	8
Rec. air pressure	kPa	500-700	-	500
Air consumption	l/min	100-200	-	100-150
Vacuum exhaust***	mm	Ø100	-	Ø100
Tank drain	DN	-	-	15
Central vacuum	mm	-	-	Ø70
Vacuum air consumption	m <sup>3</sup> /h	-	-	150
Vacuum depression	mm H <sub>2</sub> O	-	-	140
Shipping data				
	net, kg	40	30	70
	crated, kg	70	60	100
	boxed, kg	100	90	130
Dimensions in mm				
<b>A</b> Width		1440	1440	1440
<b>B</b> Depth		700	700	420
<b>C</b> Height		1650	-	-
<b>D</b>		920	920	920
<b>E</b>		420	420	900
<b>F</b>		520	520	-
<b>1</b> Electrical connection <b>2</b> Steam connection <b>3</b> Condensate <b>4</b> Air connection <b>5</b> Vacuum outlet				

\* Without compressor  
 \*\* With compressor  
 \*\*\* With vacuum

